

THERMAL/THERMAL TRANSFER BAR CODE PRINTER

RING 400PEI+SERIES



ALL MIGHTY DESK TOP PRINTER

- Experienced design makes it sharp and friendly
- 203/300DPI
- 152MM/SEC
- 32 BIT RISC CPU
- 16MB SDRAM, 8MB FLASH
- VARIOUS OPTION

RING 400PEI+Series Specification

Model Name	408PEI+	412PEI+
Print Speed	152.4mm / sec	101.6mm / sec
Resolution	203dpi	300dpi
Print Width	108.0mm	105.7mm
Print Length	4~1727mm	4~726mm
Print Method	Thermal Transfer / Direct Thermal	
Media Type	Roll Stock (continuous or die cut), Fan Fold, Tag Stock	
Media Width	25mm to 118mm	
Media Thickness	0.06~0.25mm	
Supply Roll Maximum Diameter	127.0mm	
Ribbon	Ink face-out	
Ribbon width	30mm to 110mm	
Ribbon Length	300M	
Ribbon Roll Diameter	Industry standard : 25.4mm core diameter, Maximum diameter of 68mm	
Processor	32bit RISC CPU	
Memory	16MB SDRAM, 8MB Flash	
Sensor	Die-cut label home position, black mark, no ribbon, no media	
Printer Language	ALL, RZPL	
Resident Font	11 resident Windows bit mapped font. Scalable font in 4 orientations.	
Font Download	Windows Bitmap fonts and Asian fonts	
Barcodes and 2D codes	Code 39, Code 93, Code 128(Sub set A, B, C), UCC128, UCC/EAN-128, UPC A/E(add on 2&5), Interleaved 2 of 5, EAN128,EAN8/13(add on 2&5), Codebar, PostNET, DUN14, MaxiCode, HIBC, Plessey, RPS128, PDF417, Datamatrix, QR code	
Graphics	BMP, PCX, and down loadable formats	
Interfaces	USB2.0, Ethernet, Serial	
Operation Panel	2 colored LEDs , 1 Function key	
Cabinet	Durable plastic with Black transparent media window	
Power supply	Auto Switching 100-240VAC, 50/60Hz	
Operating Temperature	5 to 40 centigrade	
Humidity	30 to 85%, non-condensing	
Approval	CE(EMC), FCC Class A, CCC, BIS, CB, CUL, BSMI	
Dimensions	171mm H x 226mm W x 285mm D	
Weight	2.7Kg	
Options	Rotary cutter Stripper Module CF Card Adapter with RTC External Label Stocker External Label Rewinder	

