

# **HC60 Handheld Computer**



This is our our newly-developed rugged handheld computer which exhibits extremely powerful performance. Built with Android 10/11.0 OS and Qualcomm high-performance processor, it features a removable large capacity battery and vigorous system configuration. It has rich functionality features for barcode scanning, RFID, NFC, front and rear cameras, etc. The device can be implemented in a wide spectrum of industries, including logistics, warehousing, retail, asset tracking, etc., assisting customers to improve operation and management levels significantly.



# **Specification**

### **Physical Characteristics**

Dimensions	159.5 x 65.7 x 16.8 mm / 6.28 x 2.58 x 0.66 in.
Weight	219 g / 7.72 oz. (device with battery)
Keypad	5 side keys : power, 2 scan keys, volume +/- Main keyboard: 22 keys (numeric keys, direction key, screen-lock key, Enter, Del, F1-F10, etc.)
Battery	4350 mAh removable main battery, 2600 mAh pistol battery (UHF version optional)
	Standby: up to 490 hours (only main battery ; WiFi: up to 470h; 4G: up to 440h) $% \left( 1-\frac{1}{2}\right) =0$
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Speaker	Support
Vibrator	Support
Microphone	2 Microphones, 1 for noise reduction
Display	4-inch (18:9), IPS LTPS 1080*540
Touch Panel	Multi-touch panel, gloves and wet hands supported
Sensor	Gravity sensor, proximity sensor, light sensor, accelerometer sensor, vibration motor
Indicator LED	Power, charging, scanning indicator
Card slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB2.0, Type-C, OTG

Derfermene	_
Performance	۳.

CPU	Qualcomm 1.8 GHz Octa-core / Cortex-A53 2.0GHz Octa-core
RAM+ROM	3 GB + 32 GB
Expansion	Supports up to 128 GB Micro SD card

#### **Developing Environment**

Operating System	Android 10 / Android 11
SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

## **User Environment**

Operating Temp.	-20 °C~+50 °C
Storage Temp.	-40 °C~+70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops to the concrete across the operating temperature range
Tumble Specification	$1000 \times 0.5$ m / 1.64 ft, falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

#### Communication

	Support 802.11 a/b/g/n/ac/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6 ;
	Fast roaming: PMKID caching, 802.11r, OKC
WLAN	Operating Channels: 2.4G(channel 1°13), 5G(channel36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132, 136,140,144,149,153,157,161,165),Depends on local regulations
	Security and Encryption: WEPWPA/WPA2-PSK(TKIP and AES),WAPI- PSK—EAP-TTLS,EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS,PEAP-GTC,etc.

WWAN	2G: 850/900/1800/1900 MHz
	3G: CDMA EVDO: BC0, BC1
	WCDMA: B1/B2/B4/B5/B8
	TD-SCDMA: A/F(B34/B39)
	4G: B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B20/B28/B38/B39/B40/B41
Vo-LTE	Support Vo-LTE HD video voice call
Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
GNSS	GPS/AGPS, GLONASS, Galileo, Internal Antenna
Data Collec	tion
Camera	
Front Camera	5MP
Rear Camera	Rear 13MP Autofocus with flash
NFC	
Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm
UHF (Optional	)
Chip-set	Impinj Indy R2000
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular Polarized Antenna (4 dBi)
Power	1W (30 dBm, +5 dBm to +30 dBm adjustable)
Power	2W Optional (33 dBm, for Latin America, etc.)
R/W range	>25 m (indoors); >15 m (open outdoors, Impinj MR6 tag)
Fastest Read Rate	900+ tags/sec
*Ranges and rates dep	pend on tags and environment
Barcode Scan	ning (optional)
2D Scanner	Zebra: SE4710
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc

#### **Optional accessories**(See details in Accessory Guide)

Wrist Strap; Rubber Bumper; Charging Cradle



台北 TEL:+886-2-2228-1000 FAX:+886-2-2228-7070 台中 TEL:+886-4-2708-1000 台中 TEL:+886-4-2708-4000 台南 TEL:+886-6-311-4000 高雄 TEL:+886-7-380-5000 FAX:+886-7-380-6000

東莞 TEL:+86-769-8533-9439 FAX:+86-769-8533-9409 尾山 TEL:+86-512-5745-3700 FAX:+86-512-5745-3703 廈門 TEL:+86-512-5745-3700 FAX:+86-512-5745-3703 www.regalscan.com.tw

